

| Product Number | Diameter-Grain Weight-Nose Type | Bullet OAL in inches | CG = Distance from crimp groove to the nose of the bullet DR = Distance from bullet nose to the top edge of the first driving ring LG = Distance from nose of the bullet to the first lube groove | | | |
|-----------------------|--|-----------------------------|--|----|--|--|
| 90300 | 311-93-1R | .509 | .229 | LG | | |
| 90301 | 311-100-2R | .578 | .298 | LG | | |
| 90311 | TL314-90-SWC | .565 | .220 | DR | | |
| 90316 | 358-105-SWC | .510 | .295 | CG | | |
| 90574 | 358-125-RF | .540 | .275 | CG | | |
| 90318 | 358-140-SWC | .643 | .295 | CG | | |
| 90279 | TL358-148-WC | .550 | | | | |
| 90312 | 358-148-WC | .577 | .105 | CG | | |
| 90328 | 358-150-1R | .643 | .288 | CG | | |
| 90321 | TL358-158-SWC | .650 | .275 | DR | | |
| 90322 | C358-158-SWC | .665 | .250 | CG | | |
| 90388 | TL358-158-2R | .710 | .245 | DR | | |
| 90303 | 358-158-RF | .630 | .360 | CG | | |
| 90305 | 358-102-1R | .464 | .264 | LG | | |
| 90239 | 356-120-TC | .555 | .280 | LG | | |
| 90464 | TL356-124-2R | .595 | .314 | DR | | |
| 90238 | TL356-124-TC | .580 | .280 | DR | | |
| 90309 | 356-125-2R | .565 | .345 | LG | | |
| 90466 | 365-95-1R | .420 | .212 | LG | | |
| 90470 | 401-145-SWC | .530 | .220 | LG | | |
| 90431 | TL401-175-SWC | .598 | .250 | DR | | |
| 90256 | 401-175-TC | .590 | .245 | LG | | |
| 90330 | 401-195-SWC | .643 | .284 | CG | | |
| 90335 | TL410-210-SWC | .658 | .283 | DR | | |
| 90336 | 429-214-SWC | .665 | .300 | CG | | |
| 90338 | C429-240-SWC | .740 | .250 | CG | | |
| 90285 | 429-200-RF | .598 | .267 | CG | | |
| 90341 | 429-240-2R | .751 | .403 | CR | | |
| 90299 | TL430-240-SWC | .737 | .275 | DR | | |
| 90858 | C430-310-RF | .830 | .320 | CG | | |
| 90570 | 452-160-RF | .435 | .210 | CG | | |
| 90348 | 452-200-SWC | .637 | .315 | LG | | |
| 90234 | 452-200-RF | .528 | .268 | CG | | |
| 90463 | TL452-200-SWC | .585 | .260 | DR | | |
| 90351 | 452-228-1R | .628 | .337 | LG | | |
| 90346 | TL452-230-2R | .660 | .365 | DR | | |
| 90287 | TL452-230-TC | .620 | .280 | DR | | |

| Product Number | Diameter-Grain Weight-Nose Type | Bullet OAL in inches | CG = Distance from crimp groove to the nose of the bullet DR = Distance from bullet nose to the top edge of the first driving ring LG = Distance from nose of the bullet to the first lube groove | | | |
|-----------------------|--|-----------------------------|--|----|--|--|
| 90290 | 452-230-TC | .620 | .280 | LG | | |
| 90356 | 452-252-SWC | .665 | .305 | CG | | |
| 90358 | 452-255-RF | .635 | .260 | CG | | |
| 90359 | C452-300-RF | .755 | .285 | CG | | |
| 90237 | C476-325-RF | .720 | .278 | CG | | |
| 90241 | 476-400-RF | .890 | .380 | CG | | |
| 90991 | C501-440-RF | .900 | .384 | CG | | |
| 90360 | C285-130-R | .890 | .470 | CG | | |
| 90362 | C309-113-F | .623 | .175 | LG | | |
| 90364 | C309-120-R | .665 | .215 | LG | | |
| 90366 | C309-150-F | .833 | .413 | CG | | |
| 90367 | C309-160-R | .900 | .480 | CG | | |
| 90368 | C309-170-F | .950 | .530 | CG | | |
| 90369 | C309-180-R | .958 | .538 | CG | | |
| 90370 | C309-200-R | 1.068 | .648 | CG | | |
| 90385 | C312-155-2R | .930 | .630 | CG | | |
| 90361 | CTL312-160-2R | .960 | .653 | CG | | |
| 90371 | C312-185-1R | 1.015 | .595 | CG | | |
| 90274 | C324-175-R | .958 | .538 | CG | | |
| 90775 | C329-205-1R | 1.039 | .564 | LG | | |
| 90372 | C338-220-1R | 1.035 | .560 | LG | | |
| 90324 | 379-250-RF | .925 | .412 | CG | | |
| 90373 | 457-340-F | .862 | .440 | CG | | |
| 90374 | 457-405-F | 1.040 | .440 | CG | | |
| 90268 | 459-405-HB | 1.100 | .480 | LG | | |
| 90375 | 457-450-F | 1.205 | .605 | LG | | |
| 90376 | C457-500-F | 1.205 | .605 | LG | | |
| 90577 | 459-500-3R | 1.415 | .685 | LG | | |
| 90255 | 515-450-F | .985 | .505 | LG | | |
| 90266 | 515-500-F | 1.050 | .464 | LG | | |

7
2
1.5
8
3
3
1.5
5
31